

STEEL

MATTE BLACK

THIS IS MATTE BLACK



FIRE RESISTANCE

Meets the requirements of AS/NZS 1530.3 Methods for Fire Tests on Building Materials.




SCRATCH RESISTANCE

No marking of paint surface when tested in accordance with AS2331.4.7, with no less than 1.5kg weight applied to the test piece.




SALT SPRAY

Meets the requirements of AS/NZS2728:2013 Sections 2.8 and 2.10.



HUMIDITY RESISTANCE

Humidity resistance - Meets the requirements of AS/NZS2728:2013 Sections 2.8 and 2.9.




QUV RESISTANCE (Durability Of Coating System)

Meets the requirements of AS/NZS2728:2013 Section 2.8 and Table 2.4. Note: Tests are conducted on a flat panel.



BEND TEST

No loss of adhesion or paint cracking when bent around a diameter equal to five times



IMPACT RESISTANCE

No loss of paint adhesion after a test piece is struck on the reverse side with a specified force of 10J, in line with the test methodology AS/NZS2728:2013 Table 2.2 and Appendix E.



ARCHITECTURAL CLADDING FLASHINGS RAINWATER GOODS CUSTOM FABRICATION

GET IN TOUCH

Phone: (03) 9331 7920

Email: sales@colorspan.com.au

Website: www.colorspan.com.au

Address: 4 Aviation Place Tullamarine 3043